

EP-PLV LED LAMP

ecOLED™

A DIVISION OF ecPOWER

FEATURES

- 360° light dispersion & 270° rotatable socket options
- Instant-start, no flickering, no humming
- 6w replaces 13w CFL
- 8w replaces 18w CFL
- 11w replaces 26w CFL



G24 POT LIGHT LED LAMP. 6, 8 and 11 watt. Numerous base choices G24D / G24Q / GX24Q / GX23 / G23 / GU24 / E26. Changes out in seconds, lasts for years

TECHNICAL SPECIFICATIONS

Housing	6060 Aluminum and hardened plastic
Finish	As shown
Ingress Protection	IP40
Mounting	G24D / G24Q / GX24Q / GX23 / G23 / GU24 / E26
Applications	Pots, hanging fixtures
Dimensions	9watt: 127mm x 35mm x 35mm 11watt: 139mm x 35mm x 35mm

OPTICAL & PERFORMANCE SPECIFICATIONS

Lumen Output	6w: 560-620L 8w: 790-850L 11w: 1180-1270L
CRI	>83
Lens	Phosphor/Clear
Beam Angles	120° 180° 360° options
L70	>50,000 hours
LM80	45°C 9000 hours 99%
LM79	Up to 100 lumens per watt
Certifications	Approved to CSA and UL standard E365384, CE & ROHS

ELECTRICAL SPECIFICATIONS

Lighting Source	2835 SMD LED's
Available Wattages	6w / 8w / 11w
Power Factor	>0.9
Ambient temperature	-25° to 40°C
Available Voltages	100-277v



info@ecopowerinc.com | ecoled.ecopowerinc.com | 1.800.564.8086



A Canadian
Manufacturer

Warranty is only valid based on fixtures operating for 12 hours or less per day.

©2019 Ecopower Inc. All rights reserved.
REV-0724.19-144912

DIMENSIONS CHART

W	L	D
6w	4.7"	2.2"
8w	4.7"	2.2"
11w	4.7"	2.2"

DIMENSIONS & BASES CHART

BEAM	WATTAGE	BASES	LENGTH W/ DIFFERENT BASES
HORIZONTAL	6W	G23/GX23	126mm
		G24/G24Q/G24D	120mm
		GU24	114mm
	8W	E26	128mm
		G23/GX23	126mm
		G24/G24Q/G24D	120mm
11W	GU24	GU24	114mm
		E26	128mm
	G23/GX23	G23/GX23	126mm
		G24/G24Q/G24D	120mm

AVAILABLE MODELS

- EP-PLV-WW-6W-V4-G24Q
- EP-PLV-WW-11W-V4-E26
- EP-PLV-N2-6W-V4-G23-L2
- EP-PLV-CW-82-V4-GU24
- EP-PLV-CW-11W-V4-GX24Q-4
- EP-PLV-11W-NW-V4-GX23
- EP-PLV-11W-CW-V4-G24Q

BASE SELECTION GUIDE

